



FS-AHD904/908/926V3

Model		FS-904	FS-908	FS-926V3
System	Compression	Standard H.264 High Profile		
	CPU	Cortex A7	Cortex A7	Cortex A9
	OS	Embedded Linux		
Video	Input	BNC × 4	BNC × 8	BNC × 16
	Resolution	AHD 2.0 1080P, 720P, WD1 real time		
	IP Input / Access Bandwidth	IPC × 1 / 6Mbps	IPC × 1 / 6Mbps	IPC × 8 / 24Mbps
	Output	HDMI × 1 : 1920 × 1080, VGA × 1 : 1920 × 1080, BNC × 1 : CVBS (used as the main or spot output)		
IP Input	Resolution	1080P / 960P / 720P	3MP / 1080P / 960P / 720P	3MP / 1080P / 960P / 720P
	Frame Rate	3MP	--	12fps (PAL) 15fps (NTSC)
		1080P/960P/720P	25fps (PAL) 30fps (NTSC)	200fps (PAL) 240fps (NTSC)
Audio	Input	RCA × 4	RCA × 4	RCA × 1
	Output	RCA × 1		
Two-way audio		Take up channel one audio input		
Record	Resolution	1080P, 1080P Lite, 720P, WD1		
	Frame Rate	1080P : 1~12fps (PAL / NTSC) 1080P Lite / 720P / WD1 : 1~real time (PAL / NTSC)		
	Bit Rate	768Kbps ~ 8Mbps		
	Encode	VBR / CBR		
	Quality	6 Level		
	Mode	Manual, timer, motion, sensor		
	File Manager	Lock, unlock		
Play back	Playback	4 CH	8 CH	16 CH
	Search	Time / calendar search, event (motion,sensor)		
	Smart Search	Highlighted date and time to display the channel record		
	Function	Play, pause, FF, FB, digital zoom		
Alarm	Mode	Sensor, motion, video loss		
	Input	4 CH	4 CH	4 CH
	Output	1 CH	1 CH	1 CH
	Triggering	Record, PTZ move, e-mail, etc		
Network	Interface	RJ45 10M / 100M × 1		
	Protocol	TCP / IP, UDP, DHCP, DNS, PPPOE, DDNS		
	Others	10 users online, dual stream		
Cell Phone	OS	iPhone, Andriod		
	Function	Multi-screen surveillance (for certain model), record, snapshot, PTZ control, save the device list		

Model		FS-904	FS-908	FS-926V3
Port	HDD	SATA × 1		
	RS485	RS485 × 1		
	USB	USB 2.0 × 2, connect to mouse and USB backup device		
	Remote Controller	Optional		
Others	Power Supply	DC 12V		
	Consumption	≤ 5W (without HDD)	≤ 8W (without HDD)	≤ 8W (without HDD)
	Dimensions (mm)	300 × 248 × 45 (W × D × H)		380 × 268 × 45
	Work Environment	-10 ~ 50 °C , 10% ~ 90% humidity		

